

CLAIM AMENDMENTS

Claim 1. (canceled)

2. (previously amended): An odometer counter, said odometer counter comprising:

an encoder, said encoder having a unique key, said key constructed and arranged to configure an encryption engine, said encoder further constructed and arranged to execute said encryption engine with an odometer value to form an encrypted odometer value, said encoder further constructed and arranged to store said odometer value in a non-volatile memory, said encoder is further constructed and arranged to increment said odometer value upon receiving an increment signal; and

a decoder, said decoder constructed and arranged to receive said encrypted odometer value from said encoder, said decoder further constructed and arranged to decrypt said encrypted odometer value and to transmit said decrypted odometer value.

3. **(previously amended):** An odometer counter, said odometer counter comprising:

an encoder, said encoder having a unique key, said key constructed and arranged to configure an encryption engine, said encoder further constructed and arranged to execute said encryption engine with an odometer value to form an encrypted odometer value, said encoder further constructed and arranged to store said odometer value in a non-volatile memory; and

a decoder, said decoder constructed and arranged to receive said encrypted odometer value from said encoder, said decoder further constructed and arranged to decrypt said encrypted odometer value and to transmit said decrypted odometer value; wherein said key is 64 bits in length.

4. **(previously amended):** An odometer counter, said odometer counter comprising:

an encoder, said encoder having a unique key, said key constructed and arranged to configure an encryption engine, said encoder further constructed and arranged to execute said encryption engine with an odometer value to form an encrypted odometer value, said encoder further constructed and arranged to store said odometer value in a non-volatile memory; and

a decoder, said decoder constructed and arranged to receive said encrypted odometer value from said encoder, said decoder further constructed and arranged to decrypt said encrypted odometer value and to transmit said decrypted odometer value; wherein said odometer value is 16 bits in length.

5. **(original):** An odometer counter as in claim 4 wherein said 16 bit odometer value is combined with another 16 bit value.

6. **(original):** An odometer counter as in claim 5 wherein said another 16 bit value is composed of a pre-defined 12 bit value and a 4 bit value based upon inputs to said encoder.

7. **(original):** An odometer counter as in claim 6 wherein said 12 bit value is stored in said non-volatile memory of said encoder.

8. **(previously amended)**: An odometer counter, said odometer counter comprising:

an encoder, said encoder having a unique key, said key constructed and arranged to configure an encryption engine, said encoder further constructed and arranged to execute said encryption engine with an odometer value to form an encrypted odometer value, said encoder further constructed and arranged to store said odometer value in a non-volatile memory; and

a decoder, said decoder constructed and arranged to receive said encrypted odometer value from said encoder, said decoder further constructed and arranged to decrypt said encrypted odometer value and to transmit said decrypted odometer value;

wherein said encrypted odometer value from said encoder is transmitted asynchronously to said decoder.

Claim 9. **(canceled)**

10. **(previously amended)**: A method for securing odometer values, said method comprising the steps of:

- (a) providing an encoder having a unique key and an encryption engine;
- (b) configuring said encryption circuit with said key;
- (c) receiving an increment signal;
- (d) incrementing an odometer value to form an incremented odometer value;
- (e) storing said incremented odometer value into said a non-volatile memory;
- (f) adding a 16-bit value to said odometer value to form a 32 bit value; ~~and~~
- (g) encrypting said 32 bit value with said encryption engine to form said encrypted odometer value;
- (h) transmitting said encrypted odometer value to a decoder; and
- (i) decrypting said encrypted odometer value with said decoder to obtain said odometer value.

11. **(previously amended)**: A method for securing odometer values, said method comprising the steps of:

- (a) providing an encoder having a unique key and an encryption engine;
- (b) configuring said encryption circuit with said key;
- (c) receiving an increment signal;
- (d) incrementing an odometer value to form an incremented odometer value;
- (e) storing said incremented odometer value into said a non-volatile memory;
- (f) encrypting said incremented odometer value with said encryption engine

to form an encrypted odometer value;

- (g) generating a data packet with said encrypted odometer value;
- (h) adding an identifier code to said data packet to form a tagged data packet;
- (i) transmitting said tagged data packet from said encoder to said decoder;

and

(j) decrypting said encrypted odometer value with said decoder to obtain said odometer value.

12. **(original)**: An odometer counter as in claim 6 wherein a portion of said 12 bit value is stored in said non-volatile memory of said encoder.

13. **(original)**: An odometer counter as in claim 6 wherein a portion of said 12 bit value is a checksum based on said odometer value.

Claims 14-26 **(canceled)**